

## PRODUCT-BULLETIN

# GRAFIPRINT BANNER D440 (Blockout)



Released on 1<sup>st</sup> November 2014

### PROVISIONAL BULLETIN

## Description

The Grafiprint Blockout Banner Material with reference D440 is a soft, exceptionally strong and self-extinguishing banner material in matt finish, developed especially to be used on solvent printers (eco/mild/hard), latex printers and UV printers, and can also be used for screenprinting.

## Characteristics

- ◆ Finish: white matt
- ◆ These products have an outdoor life expectancy up to 1 year (see product data sheet), for vertical applications and under Central-European conditions.

## Application

Grafiprint Blockout Banner Material D440 has been developed especially for short to middle-term outdoor applications up to 1 year, such as point-of-purchase and outdoor advertising. Indoors it can be used almost without any limitations.

→ *Other applications in close consultations with Grafityp !*

## Limitations

Limitations are mentioned for each product separately in the respective technical data sheets, of which you can find the most recent version on the Grafityp website ([www.grafityp.com](http://www.grafityp.com)).

## Warranty

Please consult the General Grafiprint Warranty Certificate for detailed warranty declarations of the Grafiprint print media. The most recent version of this warranty certificate will be available on the Grafityp website ([www.grafityp.com](http://www.grafityp.com)).

## Mounting Instructions

Grafityp provide trainings in various levels, enabling the customer to mount these banners in a professional and skilled way.

Detailed directives and tips can also be found in the GrafiManual and on [www.grafityp.com](http://www.grafityp.com)

## Available References

Grafiprint B440 is available in the following versions :

Product reference	Description	Thickness film
D440	White matt	350 µm

## Product Characteristics

A detailed overview of the product characteristics can be found on the respective technical data sheets, of which you can always find the most recent version on the Grafityp website ([www.grafityp.com](http://www.grafityp.com)).

## Storage Instructions

All Grafityp materials always need to be stored in their original packing and with the original protection flanges (and preferably stored vertically).

In order to avoid any loss of quality, the Grafityp materials should also be stored in suitable conditions, that is at a temperature between 10 and 20°C and a relative humidity of 50%.

Under these conditions the Grafityp materials can be stored up to two years.

## Cleaning and Maintenance

- ◆ Once the banner has reached its optimal drying (after a couple of days), the surface can be cleaned under normal conditions. Please take the following guidelines into consideration :
  - Don't use any scouring cleaning agents.
  - Don't use any cleaning agents that contain strong solvents or alcohol.
  - Don't use cleaning agents with a pH value between 3 and 11.

## Important

The information mentioned in this product bulletin is based upon tests that were executed by Grafityp and that we consider to be reliable. The information always represents an average, a minimum or a maximum value, and should be considered as such. It is only given for your information, and does not give any guarantee. Grafityp cannot be held responsible for any damage, either direct or indirect, resulting from the use of the film. It is up to the user to decide whether or not the product is suited for his particular application.

## Technical Service

If you have any technical questions with regard to the Grafityp films you can always contact our technical department :

Mr. Richard van Ochten  
Centrum-Zuid 1539  
3530 Houthalen (Belgium)  
Tel. : +32-(0)11-600850  
e-mail : [tech.sup@grafityp.com](mailto:tech.sup@grafityp.com)  
website : [www.grafityp.com](http://www.grafityp.com)