

PRODUCT-BULLETIN

GRAFIPRINT BANNER LPVC



Released on 9th March 2012
PROVISIONAL BULLETIN

Description

Grafiprint PVC Banner Material with reference LPVC is an exceptionally strong, tear- and water resistant PVC material for indoor and outdoor applications, provided with a special matt coating, which makes it printable on one side. The print coating has been developed to allow printing on most common low-volatile solvent printers (such as the Mutoh Rockhopper, the Roland Soljet, etc...).

Characteristics

- ◆ Finish: white matt
- ◆ These products have an outdoor life expectancy up to 2 years (see product data sheet), for vertical applications and under Central-European conditions.

Application

Grafiprint LPVC has been developed especially for short to middle-term outdoor applications, such as billboards, banners and decorations. Indoors it can be used almost without any limitations.

→ *Other applications in close consultation with Grafityp !*

Limitations

Limitations are mentioned for each product separately in the respective technical data sheets, of which you can find the most recent version on the Grafityp website (www.grafityp.com).

Warranty

Please consult the General Grafiprint Warranty Certificate for detailed warranty declarations of the Grafiprint print media. The most recent version of this warranty certificate will be available on the Grafityp website (www.grafityp.com).

Mounting Instructions

Grafityp provide trainings in various levels, enabling the customer to use this banner in a professional and skilled way.

Detailed directives and tips can also be found in the GrafiManual and on www.grafityp.com

Available Reference

Grafiprint LPVC is available in the following version :

Product reference	Description	Thickness film
LPVC coated	White matt	560 µm

Product Characteristics

A detailed overview of the product characteristics can be found on the respective technical data sheets, of which you can always find the most recent version on the Grafityp website (www.grafityp.com).

Storage Instructions

All Grafityp materials always need to be stored in their original packing and with the original protection flanges (and preferably stored vertically).

In order to avoid any loss of quality, the Grafityp materials should also be stored in suitable conditions, that is at a temperature between 10 and 20°C and a relative humidity of 50%.

Under these conditions the Grafityp materials can be stored up to two years.

Cleaning and Maintenance

- ◆ Once the banner has reached its optimal drying (after a couple of days), the surface can be cleaned under normal conditions. Please take the following guidelines into consideration :
 - Don't use any scouring cleaning agents.
 - Don't use any cleaning agents that contain strong solvents or alcohol.
 - Don't use cleaning agents with a pH value between 3 and 11.

Important

The information mentioned in this product bulletin is based upon tests that were executed by Grafityp and that we consider to be reliable. The information always represents an average, a minimum or a maximum value, and should be considered as such. It is only given for your information, and does not give any guarantee. Grafityp cannot be held responsible for any damage, either direct or indirect, resulting from the use of the film. It is up to the user to decide whether or not the product is suited for his particular application.

Technical Service

If you have any technical questions with regard to the Grafityp media you can always contact our technical department :

Mr. Richard van Ochten
Centrum-Zuid 1539
3530 Houthalen (Belgium)
Tel. : +32-(0)11-600850
e-mail : tech.sup@grafityp.com
website : www.grafityp.com