

## PRODUCT-BULLETIN

# GRAFIPRINT BANNER LCAN (painter's canvas)



Released on 9th March 2012

### **PROVISIONAL BULLETIN**

## Description

Grafiprint material with reference LCAN is an exceptionally strong CANVAS material, made of a combination of polyester and cotton. Grafiprint LCAN has been developed especially for indoor applications, and is provided with a special satin coating, which makes it printable on one side. The print coating has been developed to allow printing on most common solvent and low-volatile solvent printers.

## Characteristics

- ◆ Finish: white satin
- ◆ These products have an outdoor life expectancy up to 2 years (see product data sheet), for vertical applications and under Central-European conditions.

## Application

Grafiprint Canvas Material LCAN has been developed especially for printing photographs, reproductions and other works of art.

→ *Other applications in close consultation with Grafityp !*

## Limitations

Limitations are mentioned for each product separately in the respective technical data sheets, of which you can find the most recent version on the Grafityp website ([www.grafityp.com](http://www.grafityp.com)).

## Warranty

Please consult the General Grafiprint Warranty Certificate for detailed warranty declarations of the Grafiprint print media. The most recent version of this warranty certificate will be available on the Grafityp website ([www.grafityp.com](http://www.grafityp.com)).

## Mounting Instructions

Grafityp provide trainings in various levels, enabling the customer to use this canvas in a professional and skilled way.

Detailed directives and tips can also be found in the GrafiManual and on [www.grafityp.com](http://www.grafityp.com)

## Available References

Grafiprint LCAN is available in the following version :

Product reference	Description	Thickness film
LCAN coated	White satin	430 µm

## Product Characteristics

A detailed overview of the product characteristics can be found on the respective technical data sheets, of which you can always find the most recent version on the Grafityp website ([www.grafityp.com](http://www.grafityp.com)).

## Storage Instructions

All Grafiprint materials always need to be stored in their original packing and with the original protection flanges (and preferably stored vertically).

In order to avoid any loss of quality, the Grafiprint materials should also be stored in suitable conditions, that is at a temperature between 10 and 20°C and a relative humidity of 50%.

Under these conditions the Grafiprint materials can be stored up to two years.

## Cleaning and Maintenance

- ◆ Nadat de optimale droging is verkregen (na enkele dagen), kan het oppervlak onder normale omstandigheden gereinigd worden. De volgende punten zijn hierbij van belang :
  - Gebruik geen schurende reinigingsmiddelen.
  - Gebruik geen reinigingsmiddelen die sterke oplosmiddelen of alcohol bevatten.
  - Gebruik reinigingsmiddelen met een pH waarde tussen 3 en 11.

## Important

The information mentioned in this product bulletin is based upon tests that were executed by Grafityp and that we consider to be reliable. The information always represents an average, a minimum or a maximum value, and should be considered as such. It is only given for your information, and does not give any guarantee. Grafityp cannot be held responsible for any damage, either direct or indirect, resulting from the use of the film. It is up to the user to decide whether or not the product is suited for his particular application.

## Technical Service

If you have any technical questions with regard to the Grafiprint media you can always contact our technical department :

Mr. Richard van Ochten  
Centrum-Zuid 1539  
3530 Houthalen (Belgium)  
Tel. : +32-(0)11-600850  
e-mail : [tech.sup@grafityp.com](mailto:tech.sup@grafityp.com)  
website : [www.grafityp.com](http://www.grafityp.com)