

PRODUCT-BULLETIN

GRAFIPRINT PAPER (Photographic) PRINT MEDIA



Released on 12th March 2012

PROVISIONAL BULLETIN

Description

Grafiprint PHOTOGRAPHIC PAPER is a white photographic paper, provided with a special print coating, making it printable on one side. The print coating has been developed especially for VARIOUS KINDS OF PRINTERS. (see product data sheet).

Characteristics

- ◆ Finish: whit glossy and white matt.
- ◆ The product has a very long indoor life expectancy and a very limited outdoor life expectancy (for vertical applications and under Central-European conditions).

Application

Grafiprint photographic paper has been developed especially for all sorts of indoor applications (e.g. for printing photographs and posters for trade shows, etc...).

→ *Other applications in close consultations with Grafityp !*

Limitations

Limitations are mentioned for each product separately in the respective technical data sheets, of which you can find the most recent version on the Grafityp website (www.grafityp.com).

Warranty

Please consult the General Grafiprint Warranty Certificate for detailed warranty declarations of the Grafiprint print media. The most recent version of this warranty certificate will be available on the Grafityp website (www.grafityp.com).

Mounting Instructions

Grafityp provide trainings in various levels, enabling the customer to use these materials in a professional and skilled way.

Detailed directives and tips can also be found in the GrafiManual and on www.grafityp.com

Available References

Grafiprint photographic papers are available in the following versions :

Product reference	Description	Thickness paper	Weight paper/m ²
LFOT	White glossy	205 µm	195 µm
LFPM	White matt	205 µm	195 µm
LFGD	White glossy	275 µm	265 µm
FLMD	White matt	275 µm	265 µm

Product Characteristics

A detailed overview of the product characteristics can be found on the respective technical data sheets, of which you can always find the most recent version on the Grafityp website (www.grafityp.com).

Storage Instructions

All Grafiprint materials always need to be stored in their original packing and with the original protection flanges (and preferably stored vertically).

In order to avoid any loss of quality, the Grafiprint materials should also be stored in suitable conditions, that is at a temperature between 10 and 20°C and a relative humidity of 50%.

Under these conditions the Grafiprint materials can be stored up to two years.

Cleaning and Maintenance

- ◆ Just like all photographic papers, this paper can be cleaned carefully by means of a dust cloth once the inks have completely dried.

Important

The information mentioned in this product bulletin is based upon tests that were executed by Grafityp and that we consider to be reliable. The information always represents an average, a minimum or a maximum value, and should be considered as such. It is only given for your information, and does not give any guarantee. Grafityp cannot be held responsible for any damage, either direct or indirect, resulting from the use of the film. It is up to the user to decide whether or not the product is suited for his particular application.

Technical Service

If you have any technical questions with regard to the Grafiprint media you can always contact our technical department :

Mr. Richard van Ochten
Centrum-Zuid 1539
3530 Houthalen (Belgium)
Tel. : +32-(0)11-600850
e-mail : tech.sup@grafityp.com
website : www.grafityp.com