

PRODUCT-BULLETIN

GRAFIPRINT MONOMERIC PRINT FILMS



Released on 1st November 2014

PROVISIONAL BULLETIN

Description

Grafiprint MONOMERIC PRINT MEDIA are soft, seamless, monomeric calendered PVC films, especially developed to be used on solvent printers (eco/mild/hard), latex printers and UV printers. The films are provided with a pressure-sensitive acrylic adhesive. This adhesive is protected by a high-quality silicone paper.

Characteristics

- ◆ Finish: transparent, white
- ◆ Most of these products have an outdoor life expectancy up to 3 years (see product data sheet), for vertical applications and under Central-European conditions.

Application

Grafiprint monomeric print media have been developed especially for all sorts of indoor applications and short-term outdoor applications on an even surface.

→ *Other applications in close consultation with Grafityp !*

Limitations

Limitations are mentioned for each product separately in the respective technical data sheets, of which you can find the most recent version on the Grafityp website (www.grafityp.com).

Warranty

Please consult the General Grafiprint Warranty Certificate for detailed warranty declarations of the Grafiprint print media. The most recent version of this warranty certificate will be available on the Grafityp website (www.grafityp.com).

Mounting Instructions

Grafityp provide trainings in various levels, enabling the customer to mount these films in a professional and skilled way.

Detailed directives and tips can also be found in the GrafiManual and on www.grafityp.com

Available References

Grafiprint MONOMERIC print media are available in the following versionis :

Product reference	Description	Thickness film (DIN 53370)*	Thickness film+glue+paper (DIN 53370)*
S110P	Transparent glossy	80 µm	240 µm
S111P	Transparent matt	80 µm	240 µm
S112P	White glossy	100 µm	270 µm
S113P	White matt	100 µm	270 µm
S02P	Wit glossy	70 µm	210 µm
S05S	White glossy, black glue	95 µm	235 µm
S06S	White matt, black glue	95 µm	235 µm
S10P	Transparent glossy	80 µm	220 µm
S12P	White glossy	75 µm	215 µm
S12R	White glossy	75 µm	215 µm
S13P	White matt	75 µm	215 µm
S14P	White glossy, grey glue	75 µm	245 µm
L10P coated	Transparent glossy	170 µm	290 µm
L12P coated	White glossy	170 µm	290 µm

Recommended laminates

In order to achieve an excellent result, we advise you to laminate these media with one of our MONOMERIC laminates.

Product Characteristics

A detailed overview of the product characteristics can be found on the respective technical data sheets, of which you can always find the most recent version on the Grafityp website (www.grafityp.com).

Storage Instructions

All Grafiprint materials always need to be stored in their original packing and with the original protection flanges (and preferably stored vertically).

In order to avoid any loss of quality, the Grafiprint materials should also be stored in suitable conditions, that is at a temperature between 10 and 20°C and a relative humidity of 50%.

Under these conditions the Grafiprint materials can be stored up to two years.

Cleaning and Maintenance

- ◆ After its application, the film can immediately be cleaned with a dust cloth or a slightly damp cloth.
- ◆ Once the film has reached its optimal adhesive strength (after a couple of days), the surface can be cleaned under normal conditions. Please take the following guidelines into consideration :
 - Don't use any scouring cleaning agents.
 - Don't use any cleaning agents that contain strong solvents or alcohol.
 - Don't use cleaning agents with a pH value between 3 and 11.

Removal

- ◆ Self adhesive films always need to be heated in order to remove them again (from any surface).

Important

The information mentioned in this product bulletin is based upon tests that were executed by Grafityp and that we consider to be reliable. The information always represents an average, a minimum or a maximum value, and should be considered as such. It is only given for your information, and does not give any guarantee. Grafityp cannot be held responsible for any damage, either direct or indirect, resulting from the use of the film. It is up to the user to decide whether or not the product is suited for his particular application.

Technical Service

If you have any technical questions with regard to the Grafiprint films you can always contact our technical department :

Mr. Richard van Ochten
Centrum-Zuid 1539
3530 Houthalen (Belgium)
Tel. : +32-(0)11-600850
e-mail : tech.sup@grafityp.com
website : www.grafityp.com